

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7: WO 00/56632 (11) International Publication Number: **A2** B65D 83/00 (43) International Publication Date: 28 September 2000 (28.09.00) (81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, PCT/EP00/01444 (21) International Application Number: BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, 23 February 2000 (23.02.00) (22) International Filing Date: KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, (30) Priority Data: US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, 24 March 1999 (24.03.99) GB 9906640.9 AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, (71) Applicant (for all designated States except US): GLAXO MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GROUP LIMITED [GB/GB]; Glaxo Wellcome House, GA, GN, GW, ML, MR, NE, SN, TD, TG). Berkeley Avenue, Greenford, Middlesex UB6 0NN (GB). (72) Inventors; and **Published** (75) Inventors/Applicants (for US only): ANDERSON, Gregor, Without international search report and to be republished John, McLennan [GB/GB]; (GB). HAILEY, Mark, Andrew (GB). RUSSELL, David, Joseph [GB/GB]; upon receipt of that report. (GB). GODFREY, James, William [GB/GB]; Glaxo Group Ltd., Park Road, Ware, Herts SG12 0DP (GB). (74) Agent: PIKE, Christopher, Gerard; Pike & Co., Hayes Loft, 68A Hayes Place, Marlow, Buckinghamshire SL7 2BT (GB).

(54) Title: VALVE

(57) Abstract

There is provided a valve for an aerosol container. The valve comprises a valve body; within the valve body, a sealing ring and receivable by the sealing ring, a valve stem having a dispensing passage. The valve stem is slidably movable within the sealing ring from a valve-closed position to a valve-open position in which the interior of the valve body is in communication with the dispensing passage. The sealing ring is shaped such as to reduce the contact area between the sealing ring and the valve stem. Preferably, the valve is a metering valve.